

産業用PoEマトリックス

PoEインジェクタ	ポートのリンク速度	ポート数	マネージド	アンマネージ	動作温度最小最大	af/at/bt互換	PoEモード	自動パワーリセット	DMS搭載	PoE 給電総バリエーション
SI-IES-1200-LRT	10/100/1000Base-T (RJ-45)	2		○	-40/75	af/at	A			30W
SI-IES-111D-LRT	100/1000Base-SFP & 10/100/1000Base-T PoE+ (RJ-45)	2		○	-40/75	af/at	A			30W
SI-IES-121D-LRT	100/1000Base-SFP & 10/100/1000Base-T PoE+ (RJ-45)	3		○	-40/75	af/at	A			60W

PoEメディアコンバータ (0°C~標準動作温度モデル)

SPOEB10xx-100	10/100Base-TX PoE (RJ-45) ⇔ 100Base-FX	2		○	0/40	af	A/B ¹			15W
SGPOE10xx-1x0	10/100/1000Base-T PoE (RJ-45) ⇔ 1000Base-x	2		○	0/50	af	A			15W
SGPAT10xx-100	10/100/1000Base-T PoE+ (RJ-45) ⇔ 1000Base-x	2		○	0/45	af/at	A			30W
M/GE-PSW-PSE-01	10/100/1000Base-T PoE+ (RJ-45) ⇔ 100/1000Base-x SFP	2		○	0/40	af/at	A			30W

PoEスイッチ

SISPM1040-362-LRT	(4) 10/100/1000Base-T PoE+ (RJ-45) & (2) 10/100/1000Base-T (RJ-45) & (2) 1000Base-SFP	8		○	-40/75	af/at	A	○	○	120W
SISPM1040-384-LRT-C	(8) 10/100/1000Base-T PoE+ (RJ-45) & (4) 1000Base-SFP	12		○	-40/75	af/at	A	○	○	240W
SISPM1040-582-LRT	(8) 10/100/1000Base-T PoE++ (RJ-45) & (2) 1000Base-SFP	10		○	-40/75	af/at/bt	A/B	○	○	480W
SESPM1040-541-LT-AC-JP	(4) 10/100/1000Base-T PoE++ (RJ-45) 追加有& (2) 100/1000Base-SFP 追加オプション有	6		○	-40/50	af/at/bt	A/B	○	○	240W
SESPM1040-541-LT-DC-JP	(4) 10/100/1000Base-T PoE++ (RJ-45) 追加有& (2) 100/1000Base-SFP 追加オプション有	6		○	-40/50	af/at/bt	A/B	○	○	240W
SESPM1040-541-LT-PD-JP	(3) 10/100/1000Base-T PoE++ (RJ-45)&(1) SFP (1) PoE-PD90W入力が必要	5		○	-40/50	af/at/bt	A/B	○	○	85W
SISTP1040-342-LRT	(4) 10/100/1000Base-T PoE+ (RJ-45) & (2) 100/1000Base-SFP	6		○	-40/75	af/at	A			120W
SISTP1040-382-LRT	(8) 10/100/1000Base-T PoE+ (RJ-45) & (2) 100/1000Base-SFP	10		○	-40/75	af/at	A			240W
SISTP1040-382B-LRT	(4) 10/100/1000Base-T PoE+ (RJ-45) & (4) 10/100/1000Base-T(RJ-45)&(2)100/1000Base-SFP	10		○	-40/75	af/at	A	○	○	120W
SISPM1040-3166-L	(16) 10/100/1000Base-T PoE+ (RJ-45) & (4) 100/1000Base-SFP & (2)10G-SFP	22		○	-40/60	af/at	A	○	○	240W
SISPM1040-3248-L	(24) 10/100/1000Base-T PoE+ (RJ-45) & (4) 100/1000Base-SFP & (4)10G-SFP	32		○	-40/60	af/at	A	○	○	370W
SM8TAT2SA	(8) 10/100/1000Base-T PoE+ (RJ-45) & (4) 100/1000Base-SFP	12		○	0/50	af/at	A	○	○	120W
SM16TAT2SA	(16) 10/100/1000Base-T PoE+ (RJ-45) & (2) 100/1000Base-SFP	18		○	0/50	af/at	A	○	○	240W
SM24TAT2SA	(24) 10/100/1000Base-T PoE+ (RJ-45) & (2) 100/1000Base-SFP	26		○	0/50	af/at	A	○	○	370W
SM24TBT2DPB	(24) 10/100/1000Base-T PoE++ (RJ-45) & (2) 100/1000Base-SFP コンボ 10/100/1000(RJ-45)	26		○	0/40	af/at	A	○	○	820W (1640W)
SM24TAT4XB	(24) 10/100/1000Base-T PoE+ (RJ-45) & (4) 1G/10G-SFP	28		○	0/50	af/at	A	○	○	370W
SM48TAT4XA-RP	(48) 10/100/1000Base-T PoE+ (RJ-45) & (4) 1G/10G-SFP	52		○	0/50	af/at	A	○	○	820W (1640W)
SM24TAT4XB	(24) 10/100/1000Base-T PoE+ (RJ-45) & (4) 1G/10G-SFP	28		○	0/50	af/at	A	○	○	370W
SISTP1040-551-LRT	(4) 10/100/1000Base-T PoE++ (RJ-45) & (1) 100/1000Base-SFP & (1) 10/100/1000(RJ-45)	6		○	-40/75	af/at/bt HDBT	A	○	○	360W

産業用スイッチ、産業用メディアコンバータ (PoE除く)

SISTM1040-262D-LRT-B	(2) 100/1000Base-X & (16) 10/100Base-TX(RJ-45) (2) コンボSFP/RJ-45	18		○	-40/75					
SISTG10xx-211-LRT-B	(1) 1000Base-X(SC) ⇔ (1) 10/100/1000Base-T(RJ-45) 1000Base-SX/LX/SFP (3モデル)	2		○	-40/75					
SISTG1040-242-LRT	(4) 10/100/1000Base-T (RJ-45) & (2) 100/1000Base-SFP	6		○	-40/75					
SISTG1040-282-LRT	(8) 10/100/1000Base-T (RJ-45) & (2) 100/1000Base-SFP	10		○	-40/75					
M/E-ISW-FX-02(XX)	10/100Base-TX(RJ-45) ⇔ 100Base-FX(ST/SC/LC/SFP)	2		○	-40/75					
M/GE-ISW-xxx-01	10/100/1000Base-T(RJ-45) ⇔ 100Base-FX(ST/SC/LC/SFP)	2		○	-40/75					